



CBF motors srl

	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">TECHNICAL SPECIFICATIONS</th> </tr> </thead> <tbody> <tr><td>Gear ratio</td><td>1:12</td></tr> <tr><td>Nominal tension (V)</td><td>12/24</td></tr> <tr><td>Nominal load (Kg)</td><td>40/40</td></tr> <tr><td>Nominal current (A)</td><td>3.6/3.6</td></tr> <tr><td>Duty-cycle</td><td>50%/30%</td></tr> <tr><td>Maximal load (Kg)</td><td>60/80</td></tr> <tr><td>Unload speed (mm/s)</td><td>20/40</td></tr> </tbody> </table>	TECHNICAL SPECIFICATIONS		Gear ratio	1:12	Nominal tension (V)	12/24	Nominal load (Kg)	40/40	Nominal current (A)	3.6/3.6	Duty-cycle	50%/30%	Maximal load (Kg)	60/80	Unload speed (mm/s)	20/40	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">TECHNICAL SPECIFICATIONS</th> </tr> </thead> <tbody> <tr><td>Gear ratio</td><td>1:50</td></tr> <tr><td>Nominal tension (V)</td><td>12/24</td></tr> <tr><td>Nominal load (Kg)</td><td>120/120</td></tr> <tr><td>Nominal current (A)</td><td>3.2/3.2</td></tr> <tr><td>Duty-cycle</td><td>50%/30%</td></tr> <tr><td>Maximal load (Kg)</td><td>160/210</td></tr> <tr><td>Unload speed (mm/s)</td><td>5/10</td></tr> </tbody> </table>	TECHNICAL SPECIFICATIONS		Gear ratio	1:50	Nominal tension (V)	12/24	Nominal load (Kg)	120/120	Nominal current (A)	3.2/3.2	Duty-cycle	50%/30%	Maximal load (Kg)	160/210	Unload speed (mm/s)	5/10
TECHNICAL SPECIFICATIONS																																		
Gear ratio	1:12																																	
Nominal tension (V)	12/24																																	
Nominal load (Kg)	40/40																																	
Nominal current (A)	3.6/3.6																																	
Duty-cycle	50%/30%																																	
Maximal load (Kg)	60/80																																	
Unload speed (mm/s)	20/40																																	
TECHNICAL SPECIFICATIONS																																		
Gear ratio	1:50																																	
Nominal tension (V)	12/24																																	
Nominal load (Kg)	120/120																																	
Nominal current (A)	3.2/3.2																																	
Duty-cycle	50%/30%																																	
Maximal load (Kg)	160/210																																	
Unload speed (mm/s)	5/10																																	
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>STROKE</th> <th>CODE</th> </tr> </thead> <tbody> <tr><td>50 mm</td><td>A99.08.068</td></tr> <tr><td>60 mm</td><td>A99.08.069</td></tr> <tr><td>100 mm</td><td>A99.08.070</td></tr> <tr><td>120 mm</td><td>A99.08.071</td></tr> <tr><td>150 mm</td><td>A99.08.075</td></tr> <tr><td>200 mm</td><td>A99.08.072</td></tr> <tr><td>250 mm</td><td>A99.08.073</td></tr> <tr><td>300 mm</td><td>A99.08.074</td></tr> </tbody> </table>	STROKE	CODE	50 mm	A99.08.068	60 mm	A99.08.069	100 mm	A99.08.070	120 mm	A99.08.071	150 mm	A99.08.075	200 mm	A99.08.072	250 mm	A99.08.073	300 mm	A99.08.074	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>STROKE</th> <th>CODE</th> </tr> </thead> <tbody> <tr><td>50 mm</td><td>A99.08.050</td></tr> <tr><td>100 mm</td><td>A99.08.051</td></tr> <tr><td>120 mm</td><td>A99.08.052</td></tr> <tr><td>200 mm</td><td>A99.08.053</td></tr> <tr><td>250 mm</td><td>A99.08.054</td></tr> <tr><td>300 mm</td><td>A99.08.055</td></tr> </tbody> </table>	STROKE	CODE	50 mm	A99.08.050	100 mm	A99.08.051	120 mm	A99.08.052	200 mm	A99.08.053	250 mm	A99.08.054	300 mm	A99.08.055
STROKE	CODE																																	
50 mm	A99.08.068																																	
60 mm	A99.08.069																																	
100 mm	A99.08.070																																	
120 mm	A99.08.071																																	
150 mm	A99.08.075																																	
200 mm	A99.08.072																																	
250 mm	A99.08.073																																	
300 mm	A99.08.074																																	
STROKE	CODE																																	
50 mm	A99.08.050																																	
100 mm	A99.08.051																																	
120 mm	A99.08.052																																	
200 mm	A99.08.053																																	
250 mm	A99.08.054																																	
300 mm	A99.08.055																																	
Tolleranze secondo ISO 2768-1-m Dimensione 0.5 + 6 6 + 30 30-120 120-400 Angoli Sec. ISO 468																																		
Tolleranza ± 0.1 ± 0.2 ± 0.3 ± 0.5 ± 1° Ra in µm Caratteristica significativa																																		
Approvato da: V.B. Data: 30/04/03 Materiale: Tratt. superficiale		Rifer. 0010914 CAD GENERATED (Non sono ammesse correzioni manuali)																																
Disegnato da: N.L. Data: 30/04/03 Tratt. termico		Descrizione: Micro attuatore 1:12-1:50 + EMC Micro actuators 1:12-1:50 + EMC																																
		N° Disegno: VEDI TABELLA Indice: 1:1 Scala: A3																																