

Product data sheet

Specifications



APC ProtectNet standalone surge protector for analog/DSL phone lines (2 lines, 4 wires)

PTEL2

Overview

Lead time Usually in Stock

Main

Number of cables 1
Provided equipment User manual

Physical

Colour Beige
Height 10.3 cm
Width 4.7 cm
Depth 2.8 cm
Net weight 0.06 kg
Mounting preference No preference
Mounting mode Not rack-mountable

Output

Number of power socket outlets 0

Conformance

Product certifications UL listed
Standards UL 497A

Environmental

Ambient air temperature for operation -15...45 °C
Relative humidity 0...95 %
Ambient air temperature for storage -15...45 °C
Storage Relative Humidity 0...95 %

Surge Protection and Filtering

Data line protected 3-6 RJ45

Response time	1 ns common mode
Peak current	0.15 kA common mode 0.2 kA normal mode
Data line protection	RJ45 modem/fax/DSL protection (four wire dual line)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.4 cm
Package 1 Width	9 cm
Package 1 Length	2.9 cm
Package 1 Weight	0.14 kg
Number of Units in Package 2	144
Package 2 Weight	8.16 kg
Number of Units in Package 3	750
SCC14	10731304000430

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	10 years repair or replace
-----------------	----------------------------

Recommended replacement(s)